

Pipe Hangers

Pipe hangers are used to support a sprinkler piping system from the building structure. Two or more listed components may be required to form a complete hanger assembly. The specific components required depend upon the type of building construction and the pipe size.

C-Type Clamps

A type of clamp that is used to provide a load carrying connection to the flange of a building structural element, usually by use of a jaw and setscrew combination. It also provides for the attachment of a threaded rod.

Sikla GmbH, C- Type Clamps

Product Specification

Model No	Description	Hanger Rod Size, mm (in)	Nominal Pipe Size		Remarks
			mm	(in)	
TCS-0	Beam Clamp	10	20 through 100	(3/4 through 4)	
TCS-I	Beam Clamp	10	20 through 100	(3/4 through 4)	
TCS-II	Beam Clamp	12	125 through 200	(5 through 8)	
TCS OLC	Beam Clamp	10	20 through 100	(3/4 through 4)	
TCS F	Beam Clamp	10	20 through 100	(3/4 through 4)	a

Remarks:

a. Approved for M10 hanger rod only

Company Name:	Sikla GmbH & Co KG
Company Address:	Schillerstraße 5, 78595 Hausen OV, Germany
Company Website:	http://sikla.com
New/Updated Product Listing:	No
Listing Country:	Germany
Certification Type:	FM Approved
Class of Work:	1951-Pipe hangers For AS Sys